



# SHARK Waterproof Box PC

## SHARK 7" Box PC

## SHARK 10.1" Box PC



The back panel I/O is flexible for customized configuration.



Model Name		7" + 2I385HW	10.1" + 2I385HW
Dimension (mm)		184.7W x 40H x 122.5D mm	250W x 40H x 168D mm
Weight		2 Kg	2.5 Kg
Hard drive		mSATA, 2.5" HDD	mSATA, 2.5" HDD
MB		2I385HW	2I385HW
CPU		Intel Bay Trail-I E3825 1.33 GHz (Dual Core) / Intel Bay Trail-I E3845 1.91 GHz (Quad Core)	Intel Bay Trail-I E3825 1.33 GHz (Dual Core) / Intel Bay Trail-I E3845 1.91 GHz (Quad Core)
Chipset			
Memory	Type / Capacity	E3825 DDR3L 1066MT/s E3845 DDR3L 1333MT/s	E3825 DDR3L 1066MT/s E3845 DDR3L 1333MT/s
	SO-DIMM	N/A	N/A
	On board memory	2 / 4GB	2 / 4GB
SSD Storage	CF (CFast)	N/A	N/A
	mSATA	Yes	Yes
	On Board SSD	N/A	N/A
VGA		Yes	Yes
DVI / HDMI		N/A	N/A
USB		5	5
COM		4	4
Mini-PCIe		2	2
SIM Card Holder		N/A	N/A
GPIO		4DI / 4DO (Optional)	4DI / 4DO (Optional)
Ethernet		Intel GbE x 2	Intel GbE x 2
Audio		Line-out / Mic-in (Optional)	Line-out / Mic-in (Optional)
Power Input		Wide Range +9~36V	Wide Range +9~36V
Battery		option	option
Mounting		VESA 75 & Panel Mount	VESA 75 & Panel Mount
Panel frame water proof		IP66 / IP67	IP66 / IP67
Optional MB		2I268H / 2I847H	2I268H
Expansion		GPS, 3G / 4G, Bluetooth, WI-FI	GPS, 3G / 4G, Bluetooth, WI-FI
Operating Temp.		-20°C~60°C for mSATA / SSD HDD	-20°C~60°C for mSATA / SSD HDD
Operating Humidity		5~90% @ 39°C, non-condensing	5~90% @ 39°C, non-condensing