

6GK6041-6PT2.-.... RUGGEDCOM RS416P

Technical Data

Product-type designation	RUGGEDCOM RS416P
Product description	<p>serial device server with an integrated fully managed Ethernet switch, 128-bit Encryption, up to 16 serial ports & up to 4 Ethernet ports with PoE (802.3af) Copper or Fiber options, Supports IEEE 1588 v2, Non-blocking, store and forward switching</p> <p>THE RUGGEDCOM RS416P IS AN INDUSTRIALLY HARDENED SERIAL DEVICE SERVER WITH AN INTEGRATED, FULLY MANAGED, ETHERNET SWITCH, DESIGNED TO OPERATE RELIABLY IN ELECTRICALLY HARSH AND CLIMATICALLY DEMANDING ENVIRONMENTS. 128-BIT ENCRYPTION; UP TO 16 SERIAL PORTS & UP TO 4 ETHERNET PORTS WITH POE (802.3AF) COPPER OR FIBER OPTIONS; SUPPORTS IEEE 1588 V2; NON-BLOCKING, STORE AND FORWARD SWITCHING</p>



Transmission rate	
Transfer rate	
<ul style="list-style-type: none"> • 1 	10 Mbit/s
<ul style="list-style-type: none"> • 2 	100 Mbit/s
Transfer rate	
<ul style="list-style-type: none"> • in accordance with RS 232 	300...115200 bit/s
<ul style="list-style-type: none"> • in accordance with RS 422/485 	300...115200 bit/s
<ul style="list-style-type: none"> • according to V.90 	56000 bit/s

Interfaces	
Number of electrical/optical connections / for network components or terminal equipment / maximum	4
Number of electrical connections	
<ul style="list-style-type: none"> • for network components and terminal equipment 	4
<ul style="list-style-type: none"> • maximum 	4
<ul style="list-style-type: none"> • for Power-over-Ethernet / for network components or terminal equipment 	4

<ul style="list-style-type: none"> for serial interfaces / in accordance with RS 232/RS 422/RS 485 / maximum 	16
<ul style="list-style-type: none"> for signaling contact 	1
<ul style="list-style-type: none"> for power supply 	1
<ul style="list-style-type: none"> for redundant power supply 	1
Design of electrical connection	
<ul style="list-style-type: none"> for network components and terminal equipment 	RJ45-Port, SUB-D 9 pin
<ul style="list-style-type: none"> for Power-over-Ethernet / for network components or terminal equipment 	RJ45-Port
<ul style="list-style-type: none"> for signaling contact 	10-pole terminal block
<ul style="list-style-type: none"> for power supply 	10-pole terminal block
Number of optical connections / for network components or terminal equipment / maximum	2
Number of optical connections / for fiber-optic cables	
<ul style="list-style-type: none"> at 10 Mbit/s 	4
<ul style="list-style-type: none"> at 100 Mbit/s 	4
Design of optical interface / for optical waveguide	
<ul style="list-style-type: none"> at 10 Mbit/s 	ST-Port (BFOC-Port)
<ul style="list-style-type: none"> at 100 Mbit/s 	ST-/SC-/MTRJ-/LC-Port
Range / at the optical interface / depending on the optical fiber used	2...90 km
Signal-Inputs/outputs	
Operating voltage / of signaling contacts / at AC / rated value	250 V
Operating current / of signaling contacts / at AC / maximum	0.4 A
Operating voltage / of signaling contacts / at DC / rated value	30 V
Operating current / of signaling contacts / at DC / maximum	2 A
Supply voltage, current consumption, power loss	
product options / wide range power supply	Yes
Type of voltage / 1 / of the supply voltage	DC
Supply voltage / 1	
<ul style="list-style-type: none"> rated value 	24 V
<ul style="list-style-type: none"> rated value 	18...36 V
Type of voltage / 2 / of the supply voltage	DC
Supply voltage / 2	
<ul style="list-style-type: none"> rated value 	48 V
<ul style="list-style-type: none"> rated value 	36...59 V
Type of voltage / 3 / of the supply voltage	DC
Supply voltage / 3	
<ul style="list-style-type: none"> nominal value 	110 V
<ul style="list-style-type: none"> rated value 	88...300 V

Type of voltage / 4 / of the supply voltage	AC
Supply voltage / 4	
<ul style="list-style-type: none"> rated value 	85...265 V
Product component / fusing at power supply input	Yes
Power loss	
<ul style="list-style-type: none"> maximum 	15 W
Permitted ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> during operating 	-40...+85 °C
<ul style="list-style-type: none"> during storage 	-40...+85 °C
<ul style="list-style-type: none"> during transport 	-40...+85 °C
<ul style="list-style-type: none"> Comment 	A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Coating	conformal coating optional
operating condition / fanless operation	Yes
Protection class IP	IP40
Design, dimensions and weight	
Design	19-inch rack
Width	466.7 mm (18.37 in)
Height	44 mm (1.73 in)
Depth	315 mm (12.4 in)
Net weight	5.2 kg
Material / of the enclosure	18 AWG galvanized steel enclosure
Type of mounting	
<ul style="list-style-type: none"> 35 mm DIN rail mounting 	Yes
<ul style="list-style-type: none"> S7-300 rail mounting 	No
<ul style="list-style-type: none"> Installation 19 inch 	Yes
<ul style="list-style-type: none"> wall mounting 	Yes
product component part / integrated / Ethernet switch	No
product function	
<ul style="list-style-type: none"> DNP 3.0 to DNP conversion via UDP/TCP 	Yes
<ul style="list-style-type: none"> Modbus RTU to Modbus TCP conversion 	Yes
<ul style="list-style-type: none"> RAW socket mode for any serial protocols 	Yes
Protocol / is supported	
<ul style="list-style-type: none"> DNP3 	Yes
<ul style="list-style-type: none"> GVRP 	Yes
<ul style="list-style-type: none"> HTTP 	Yes
<ul style="list-style-type: none"> Modbus TCP 	Yes
<ul style="list-style-type: none"> TFTP 	Yes
Product function / CLI	Yes
Product function / RMON	Yes

Product function / web-based management	Yes
Protocol / is supported / Telnet	Yes
Product function / MIB support	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • SNMP v3 	Yes
product function / for MIB-support	
<ul style="list-style-type: none"> • by BRIDGE-MIB 	RFC1493
<ul style="list-style-type: none"> • by IF-MIB 	RFC2863
<ul style="list-style-type: none"> • by RMON-MIB 	RFC2819
<ul style="list-style-type: none"> • by RSTP-MIB 	draft-ietf-bridge-bridgemib-smiv2-03
<ul style="list-style-type: none"> • by SNMPv2-MIB 	RFC1907
<ul style="list-style-type: none"> • by SNMPv2-SMI 	RFC2578
<ul style="list-style-type: none"> • by SNMPv2-TC 	RFC2579
<ul style="list-style-type: none"> • by TCP-MIB 	RFC2012
<ul style="list-style-type: none"> • by UDP-MIB 	RFC2013
Product function / VLAN - port based	Yes
Product function	
<ul style="list-style-type: none"> • DHCP Option 82 	Yes
product function	
<ul style="list-style-type: none"> • redundancy procedure MSTP 	No
<ul style="list-style-type: none"> • RSTP redundancy protocol 	Yes
<ul style="list-style-type: none"> • eRSTP 	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • MSTP 	No
<ul style="list-style-type: none"> • RSTP 	Yes
Protocol / is supported / SSL	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • NTP 	No
<ul style="list-style-type: none"> • SNTP 	Yes
Standards, specifications, approvals	
Standard	
<ul style="list-style-type: none"> • for EMC 	FCC Part 15 (Class A), EN55022 (CISPR22 Class A)
<ul style="list-style-type: none"> • for safety / of CSA and UL 	UL 60950-1, CSA C22.2 no. 60950-7
<ul style="list-style-type: none"> • for hazardous area / of CSA and UL 	Hazardous Locations: Class 1 Division 2
<ul style="list-style-type: none"> • for emitted interference 	EN 61000-6-4 (Class A)
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-2
Laser protection class	Complies with 21 CFR Chapter 1, Subchapter J
Verification of suitability	EN 61000-6-2, EN 61000-6-10
Verification of suitability	

• regarding NEMA	TS 2
• CE mark	Yes
• C-Tick	No
• IEC 61850-3	Yes
Further Information / Internet Links	
Internet link	
• to website	
• Industry Mall/RUGGEDCOM Selector	http://ruggedcom-selector.automation.siemens.com
• Industry Mall	http://www.siemens.com/industrial-controls/mall
• selection instrument cables and connectors	http://www.siemens.com/snst
• CAx-Download-Manager	http://www.siemens.com/cax
• industrial communication	http://www.siemens.com/simatic-net
• Information und Download Center	http://www.siemens.com/automation/net/catalog
• image database	http://automation.siemens.com/bilddb
• Industry Online Support	http://support.automation.siemens.com
letzte Änderung:	Feb 24, 2014