

ReliaGATE 20-26, Powered by Red Hat®

- Truly Industrial
- Ready for Global Deployment
- Reliable Performance, Flexible Configurations
- Customizable to Your Needs
- Open Source Platform
- Edge Computing and Integration



POWERED BY RED HAT

FEATURES

Truly Industrial - Extended operating temperature, wide range power supply with surge and sag protection, isolated and protected DIO, protected USB and serial

Ready for Global Deployment - Features support Eurotech's ReliaCELL 10-20, the global cellular module with global carrier precertifications

Reliable Performance - Powerful and efficient: single, dual and quad core Intel Atom™ E38xx, with ECC memory for additional protection

Customizable to Your Needs - Flexible: personalization and full customization options are available, ranging from branding ("skin" and color) to deep HW/SW configurations

Open Software Platform - Truly open, provides a programmable Java/OSGi gateway middleware, to free the developer from proprietary solutions

Edge Computing and Integration - Message routing and transformation, data filtering and aggregation, rules-based actions, providing intelligence at the edge

The ReliaGATE 20-26, powered by Red Hat®, is a high-performance, globally certified, IoT gateway for industrial and lightly rugged applications.

It features up to four cores, extended operating temperature support, wide range power supply, isolated and protected I/O interfaces, and customizable connectivity options.

To add global cellular connectivity and GPS, just plug in Eurotech's ReliaCELL 10-20, the carrier-certified module that enables immediate deployment (also available: internal cellular and GPS option - contact us for MOQ).

The ReliaGATE 20-26 comes with Everyware™ Software Framework (ESF), a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/OSGi middleware for IoT gateways.

Distributed and supported by Eurotech, ESF adds advanced security, diagnostics, provisioning, remote access, and full integration with Everyware™ Cloud (EC), Eurotech's IoT Integration Platform (separately available).

The ReliaGATE 20-26, powered by Red Hat, is tightly integrated Red Hat JBoss® Fuse, an open source, lightweight and modular integration platform and Red Hat JBoss BRMS, an open source rules management system. The ReliaGATE 20-26 runs on Red Hat Enterprise Linux, providing enterprise-grade reliability.

Used stand-alone, or in conjunction with EC, the ReliaGATE 20-26 provides a fast go-to-market solution for projects of any size.

Specifications

PROCESSOR	CPU	E3815, 1.46GHz, Single Core	E3827, 1.75GHz, Dual Core	E3845, 1.91GHz, Quad Core	
	MEMORY	RAM	2GB, 1333MHz, (DDR3L-ECC)		4GB, 1333MHz, (DDR3L-ECC)
STORAGE	Embedded	8GB eMMC			
	SATA	1xSATA, 1x mSATA (factory option)			
	Other	1x microSD Slot (User Accessible)			
I/O INTERFACES	Ethernet	2x 10/100/1000Mbps			
	USB	1x Host 3.0 , 1x Host 2.0, 1x ReliaCELL (Noise and Surge Protected)			
	Serial	2x RS-232/RS-422/RS-485 (9 Wires, Noise and Surge Protected), 1x Serial Console TTL			
	CAN 2.0B	1x CAN bus with 5V (100mA) Power Out			
	Digital I/O	3x Digital Input 7-35VDC, 1KV optoisolated - 3x Digital Output (40VDC), 20mA sink			
	Video	1x mini DisplayPort			
	Audio	Factory option			
	EXPANSION	miniPCle Slots	3	2	3
RADIO INTERFACES	Cellular	Eurotech ReliaCELL 10-20 (carrier pre-certified) / Factory option (miniPCle)			
	GPS	Eurotech ReliaCELL 10-20 / Factory option			
	Wi-Fi / BT	No	b/g/n, BLE	No	b/g/n, BLE
	RTC	Yes (User Accessible Battery)			
OTHER	Ext. watchdog	Yes			
	EEPROM	256kbit			
	Sensors	Temperature, Accelerometer			
	LEDs	1x Power, 3x miniPCle Slot, 2x Programmable (Dual Color Green/Amber)			
	Buttons	1x Reset, 1x Programmable			
POWER	Input	7-35VDC (Nominal 12VDC), Surge and Sag Protection, Vehicle Ignition Input			
	Consumption	7W Idle	10W Idle	12W Idle	
	Operating Temp	- 20 to +60°C	- 40 to +75°C		
ENVIROMENT	Storage Temp	- 40 to +85°C			
	Regulatory	CE, FCC, UL, IC, PTCRB			
	Environmental	RoHS2; REACH			
	Wi-Fi/BT Radio	CE - EN300 328 (2.4 Ghz ISM), EN50371 (EMI), EN301 489 (EMC) FCC - 15.209 (General RF device), 15.247 & 15.249 (2.4 GHz ISM)			
CERTIFICATIONS	Cellular	Worldwide, with Carrier Certifications (See Eurotech ReliaCELL 10-20)			
	Ingress	IP40			
	MECHANICAL	Enclosure	Anodized Aluminium (Contact us for custom enclosure color and skins)		
	Dimensions	192x131x52mm (WxDxH)			
SOFTWARE					
OS	Red Hat Enterprise Linux 7				
SDK	Red Hat JBoss Developer Studio - Red Hat Enterprise Linux Developer Suite				
Integration Platform	Red Hat JBoss Fuse				
Rules Mgmt	Red Hat JBoss BRMS				
IoT Framework	Everyware Software Framework (Java/OSGi)				

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.